

Erledigt

Boot nur mit BootArg -x

Beitrag von „Altemirabelle“ vom 14. März 2018, 21:57

Versuche zuerst herausfinden was stört.

Starte mit verbose und beobachte was am Ende kommt, ist vermutlich eine Erweiterung wie Lilu (?).

Mit -x kannst du efi nicht mounten. Aber versuchen kannst du es mit Terminal (oder tools ausprobieren wie EFI Mounter V3):

To mount an EFI boot partition, follow these steps:

1. Discover the volume identifier for your EFI boot partition.

Run this command:

```
diskutil list
```

The output should look something like this:

```
/dev/disk0
#: TYPE NAME SIZE IDENTIFIER
0: GUID_partition_scheme *251.0 GB disk0
1: EFI 209.7 MB disk0s1
2: Apple_HFS Macintosh HD 250.1 GB disk0s2
3: Apple_Boot Recovery HD 650.0 MB disk0s3
```

In this case, the volume identifier of the EFI partition is **disk0s1**

2. Create a mount point.

A mount point is a directory where a non-booted volume is mounted. On Mac OS X, mount points are typically created in /Volumes. We can create a directory called efi within /Volumes by running the following command:

```
mkdir /Volumes/efi
```

3. Mount the EFI partition at the efi mount point.

Run the command:

```
sudo mount -t msdos /dev/disk0s1 /Volumes/efi
```