

OpenCore Bootloader

Beitrag von „roddy20“ vom 13. April 2019, 21:03

installing boot sectors sample

Code

```
1. boot0af=~/src/UDK2018/Clover/CloverPackage/sym/CloverCD/usr/standalone/i386/boot0af;
2. boot1f32=~/src/UDK2018/Clover/CloverPackage/sym/CloverCD/usr/standalone/i386/boot1f32;
3. diskutil umount ${bootdisk}s1;
4. sudo dd if=${bootdisk} count=1 of=origMBR;
5. cp -fv origMBR newMBR;
6. dd if=$boot0af of=newMBR bs=1 count=440 conv=notrunc;
7. sudo dd if=newMBR of=${bootrdisk} count=1;
8. sudo fdisk -f newMBR -u -y ${bootrdisk};
9. cp -fv $boot1f32 newBS;
10. dd if=origBS of=newBS skip=3 seek=3 bs=1 count=87 conv=notrunc;
11. sudo dd if=newBS of=${bootdisk}s1 count=1;
12. diskutil mount ${bootdisk}s1;
```

Alles anzeigen

Code

```
1. bootdisk is /dev/diskN
2. bootrdisk is /dev/rdiskN
3. boot0af and boot1f32 from Clover installer or Clover boot cd
```