

Hilfe bei Installation - Ich weiß nicht mehr weiter :(

Beitrag von „Riconr1“ vom 29. März 2020, 14:46

2 x: 500 GB Kingston SA2000M8/500G M.2 2280 PCIe 3,0 x4 NVMe 3D-NAND TLC.

Noch eine weitere Frage. Da ich die RX580 nutze, ist da der Eintrag iMac18,1 korrekt?

Ich komme darauf, weil wenn ich mit Sanity Checker die plist überprüfe dann bekomme ich folgende Hinweise:

DeviceProperties

Add

- AAPL,ig-platform-id = *-blank-* - iGPU may not be set correctly. Please read the [DeviceProperties Docs](#)

Tools

- You can remove the tool EFIs here

Generic

- SpoofVendor = Yes
- AdviseWindows = No
- SystemProductName = iMac18,1
- MLB should be set to your generated board serial. See [PlatformInfo Docs](#)
- ROM = 112233000000 You should set this to your NIC MAC address. See [PlatformInfo Docs](#)
- SystemSerialNumber should be set to your generated system serial number. See the [PlatformInfo Docs](#)
- SystemUUID should be set to your generated SmUUID. See the [PlatformInfo Docs](#)

Drivers

- HfsPlus.efi Check the filename in your Drivers/ directory. Normally this is called HFSPlus.efi
- Need either VBoxHfs.efi or HFSPlus.efi here
- FwRuntimeServices.efi
- ApfsDriverLoader.efi
- NvmExpressDxe.efi should not be here!
- XhciDxe.efi should not be here!

- AppleUsbKbDxe.efi Unless you are doing a legacy install, you don't need this
- VirtualSmc.efi was absorbed into Opencore under the quirk AppleSmcIo!
- HiiDatabase.efi
- UsbKbDxe.efi

Input

- KeyForgetThreshold = 5
- KeyMergeThreshold = 2
- KeySupport = Yes
- KeySupportMode = Auto
- KeySwap = No
- PointerSupport = No
- PointerSupportMode = ASUS but should normally be *-blank-*
- TimerResolution = 50000

Output

- TextRenderer = BuiltinGraphics
- ConsoleMode = *-blank-*
- Resolution = Max
- ClearScreenOnModeSwitch = Yes but should normally be No
- IgnoreTextInGraphics = Yes but should normally be No
- ProvideConsoleGop = Yes
- DirectGopRendering = No
- ReconnectOnResChange = No
- ReplaceTabWithSpace = No
- SanitiseClearScreen = Yes
-