

# **Brauche Hilfe, hänge bei ApplePS2Controller: Notification consumer published: ApplePS2Mouse + ACPI Errors**

**Beitrag von „hectorox“ vom 4. März 2021, 20:34**

Hallo zusammen,

Ich bin am verzweifeln... .

Wollte zu OpenCore umsteigen (0.6.7) und bin dem Tutorial von Dortania's OpenCore Install Guide gefolgt, langsam und aufmerksam. Leider habe ich es noch nicht ins Setup geschafft und bleibe bei "ApplePS2Controller: Notification consumer published: ApplePS2Mouse" gefolgt von ACPI loop Errors hängen. Ich vermute es ist etwas simples und hat möglicherweise etwas mit dem Device (EC) zu tun. Mittlerweile habe ich keine Ideen mehr und vielleicht kann mir jemand von euch helfen?

So sieht der Bootvorgang aus:

```
Wooled2CControllerDriver:pci18006,9d61 Found valid Synopsys component, continuing with initialization
Wooled2CControllerHub:pci18006,9d61 S50N not implemented in ACPI tables
Wooled2CControllerHub:pci18006,9d61 FN0N not implemented in ACPI tables
Wooled2CControllerDriver:pci18006,9d61 Warning: Error getting bus config, using defaults where necessary
Wooled2CControllerDriver:pci18006,9d61 Publishing device nodes
AppleIOPICReset failed: 0 (x data) ReleaseIOPIC file: /AppleInternal/BuildRoot/Library/Caches/com.apple.xbs/Sources/IOPICFamily/IOPICFamily-537.60.1/Common/IOPICController.cpp line 100
virtual IOPICReturn IOPICController::CreateSubmissionQueue(uint16_t, uint8_t):2007:SQ Index=0 entrySize=64
virtual IOPICReturn IOPICController::CreateSubmissionQueue(uint16_t, uint8_t):2007:SQ Index=1 entrySize=64
apfs_vfs_start:2436: load: com.apple.filesystems.apfs, v1677.01.1, apfs-1677.01.1, 2021/01/24
ApplePS2Controller: Notification consumer published: ApplePS2Controller
ApplePS2Controller: Notification consumer published: ApplePS2Keyboard
ApplePS2Controller: Timed out on mouse input stream.
ApplePS2Controller: Timed out on mouse input stream.
WooledPS2Trackpad: Identify TouchPad command returned incorrect byte 2 (of 3): 0x00
ApplePS2Controller: Notification consumer published: ApplePS2Mouse
IOPIC Exception: RE_IOPIC_PARAMETER, Returned by Handler for [EmbeddedControl] (20160930/evregion-300)
[GBW] 000012 #0020: IDV

Initialized Local Variables for method [GBW]:
  Local0: ffffffff37fd21ad <Obj> Integer 0000000000000000
No Arguments are initialized for method [GBW]

IOPIC Error: Method parse/execution failed [\SB,PCIB,LPCB,EC,GBW] (Node ffffffff37fded030), RE_IOPIC_PARAMETER (20160930/pparse-632)
IOPIC Error: Method parse/execution failed [\SB,PCIB,LPCB,EC,_Q00] (Node ffffffff37fdacba0), RE_IOPIC_PARAMETER (20160930/pparse-632)
IOPIC Exception: RE_IOPIC_PARAMETER, Returned by Handler for [EmbeddedControl] (20160930/evregion-300)
[GBW] 000012 #0020: IDV

Initialized Local Variables for method [GBW]:
  Local0: ffffffff37fc7789 <Obj> Integer 0000000000000000
No Arguments are initialized for method [GBW]

IOPIC Error: Method parse/execution failed [\SB,PCIB,LPCB,EC,GBW] (Node ffffffff37fded030), RE_IOPIC_PARAMETER (20160930/pparse-632)
IOPIC Error: Method parse/execution failed [\SB,PCIB,LPCB,EC,_Q00] (Node ffffffff37fdacba0), RE_IOPIC_PARAMETER (20160930/pparse-632)
IOPIC Exception: RE_IOPIC_PARAMETER, Returned by Handler for [EmbeddedControl] (20160930/evregion-300)
[GBW] 000012 #0020: IDV

Initialized Local Variables for method [GBW]:
  Local0: ffffffff37fc7789 <Obj> Integer 0000000000000000
No Arguments are initialized for method [GBW]

IOPIC Error: Method parse/execution failed [\SB,PCIB,LPCB,EC,GBW] (Node ffffffff37fded030), RE_IOPIC_PARAMETER (20160930/pparse-632)
IOPIC Error: Method parse/execution failed [\SB,PCIB,LPCB,EC,_Q00] (Node ffffffff37fdacba0), RE_IOPIC_PARAMETER (20160930/pparse-632)
IOPIC Exception: RE_IOPIC_PARAMETER, Returned by Handler for [EmbeddedControl] (20160930/evregion-300)
[GBW] 000012 #0020: IDV

Initialized Local Variables for method [GBW]:
  Local0: ffffffff37fc7789 <Obj> Integer 0000000000000000
No Arguments are initialized for method [GBW]

IOPIC Error: Method parse/execution failed [\SB,PCIB,LPCB,EC,GBW] (Node ffffffff37fded030), RE_IOPIC_PARAMETER (20160930/pparse-632)
IOPIC Error: Method parse/execution failed [\SB,PCIB,LPCB,EC,_Q00] (Node ffffffff37fdacba0), RE_IOPIC_PARAMETER (20160930/pparse-632)
IOPIC Exception: RE_IOPIC_PARAMETER, Returned by Handler for [EmbeddedControl] (20160930/evregion-300)
[GBW] 000012 #0020: IDV

Initialized Local Variables for method [GBW]:
  Local0: ffffffff37fc7789 <Obj> Integer 0000000000000000
No Arguments are initialized for method [GBW]

IOPIC Error: Method parse/execution failed [\SB,PCIB,LPCB,EC,GBW] (Node ffffffff37fded030), RE_IOPIC_PARAMETER (20160930/pparse-632)
IOPIC Error: Method parse/execution failed [\SB,PCIB,LPCB,EC,_Q00] (Node ffffffff37fdacba0), RE_IOPIC_PARAMETER (20160930/pparse-632)
IOPIC Exception: RE_IOPIC_PARAMETER, Returned by Handler for [EmbeddedControl] (20160930/evregion-300)
[GBW] 000012 #0020: IDV

IOPIC Error: Method parse/execution failed [\SB,PCIB,LPCB,EC,GBW] (Node ffffffff37fded030), RE_IOPIC_PARAMETER (20160930/pparse-632)
IOPIC Error: Method parse/execution failed [\SB,PCIB,LPCB,EC,_Q00] (Node ffffffff37fdacba0), RE_IOPIC_PARAMETER (20160930/pparse-632)
IOPIC Exception: RE_IOPIC_PARAMETER, Returned by Handler for [EmbeddedControl] (20160930/evregion-300)
[GBW] 000012 #0020: IDV
||
```

Das Gerät ist ein Elitebook 820 G4:

i7-7500U Kaby Lake

Intel HD Graphics 620 (ich merke gerade, dass ich die Grafiksection in der config.plist falsch konfiguriert habe, dachte das wäre UHD, hat aber mit dem Problem erstmal hier nichts zu tun)

16GB DDR4 Ram

Samsung PM951 NVMe 512GB

Im Anhang findet ihr mein EFI Ordner (+DSDT)

Freue mich über jede Hilfe!